



شركة مصفاة البترول الاردنية المساهمة المحدودة

عمان - الأردن

مناقصة: رقم (142 / 2026) طلب المواد رقم (26010514) (توريد وحدات إنارة)

الموضوع: - دعوة للاشتراك في مناقصة محلية

ترغب شركة مصفاة البترول الاردنية بشراء المواد المبينة تفصيلها ومواصفاتها الفنية في الكشف المرفق وباعتباركم مورداً لهذه المواد نوجه هذه الدعوة لكم للاشتراك بالمناقصة اعلاه وتقديم عرض سعر للمواد المطلوبة مع الالتزام بكافة الشروط والمواصفات المطلوبة، وفيما يلي الشروط العامة للمناقصة: -

1. تقديم عرض الأسعار على (نسختين) قبل الموعد المحدد لإغلاق المناقصة ضمن ظرف مغلق ومختوم مبينا عليه رقم المناقصة وتاريخ الاغلاق واسم وعنوان المناقص ويسلم باليد الى (دائرة المشتريات الإدارة العامة - جبل عمان - الدوار الأول) ولا يقبل اي عرض يرسل بالفاكس نهائياً.
2. يجب ان يكون عرض الاسعار مروس باسم وعنوان المورد موقعاً ومختوماً بالخاتم الرسمي للمناقص ومرفقاً بصورة الشروط موقعة ومختومة لتأكيد التزامكم بكافة الشروط والمواصفات وكذلك تقديم صورة من السجل التجاري ورخصة المهن سارية المفعول.
3. على المناقص تثبيت الاسعار الافردية والاجمالية في عرض الاسعار رقما وكتابة بخط واضح دون تصحيح او كشط او محو او تعديل.
4. على المناقص بيان الشروط التالية في عرض الأسعار وبشكل واضح: -
 - شمول السعر لضريبة المبيعات 16% او اية نسبة تحدد بعرض السعر والرسوم الجمركية.
 - في حال وجود اي خدمة اضافية يراد تقديمها في العرض وغير واردة في مواصفات طلب المواد يجب ان يتم ذكرها بالتفصيل وان يتم بيان كلفتها المالية بشكل واضح.
 - مدة صلاحية الأسعار يجب الا تقل عن (60) يوم من تاريخ اغلاق المناقصة وخلاف ذلك يحق لشركة مصفاة البترول استبعاد العرض.
 - اجور النقل الى مستودعاتنا موقع المصفاة الزرقاء .
 - ان تكون المواد المعروضة جديدة وغير مستعملة او مجددة وخالية من العيوب مع بيان سنة الصنع.
 - تحديد منشأ البضاعة والالتزام بتقديم شهادة بلد المنشأ عند توريد المواد (مصدقة اصولاً او تشير للبيان الجمركي) وتحديد اسم الشركة الصانعة، مده التوريد، مكان التسليم
5. الشركة غير ملزمة بالإحالة على اقل الاسعار ويحق لها رفض اي عرض دون ابداء الاسباب.

س/

س/

س/



شركة مصفاة البترول الاردنية المساهمة المحدودة

عمان - الأردن

6. يحق للشركة الغاء المناقصة او اعادة طرحها او شراء جزء منها او التعديل على الكميات المطلوبة دون بيان الاسباب ودون ان تتحمل اي مسؤولية أياً كان نوعها.
7. على المناقص عدم مراجعة اي جهة فنية في الشركة الا بالتنسيق مع دائرة المشتريات.
8. المواد المطلوبة خاضعة للزيادة والنقصان بنسبة $\pm 25\%$.
9. على المناقص الالتزام بقبول الإحالة الجزئية.
10. على المناقص الالتزام بتقديم عينات مجانية للمواد المعروضة في حال طلبها حسب ما هو مطلوب وشهادات الفحص المبينة في الشروط المرفقة او كتالوجات لأي من البنود المطلوبة مع العرض.
11. على المناقص الالتزام بدفع قيمة طوابع الواردات والبالغة (6) بالآلف على قرار الاحالة خلال عشرة ايام من تبليغه بقرار الإحالة.
12. على المناقص تقديم كفالة حسن تنفيذ غير مشروطة بنسبة 10% من القيمة الاجمالية بعد تبليغه بقرار الاحالة تبقى سارية المفعول لحين استلام المواد والموافقة عليها.
13. يتم دفع ثمن المواد المشتراة بعد استلام المواد في مستودعات الشركة وبعد صدور سند استلام يؤكد استلامها كاملة ومطابقة للشروط والمواصفات.
14. في حال تأخير توريد او تنفيذ المناقصة حسب ما تم الاتفاق عليه يترتب عليكم غرامة قدرها (20) دينار أردني عن كل يوم تأخير على ان لا تتجاوز 5% من قيمة الإحالة.
15. في حال اخلال المتعهد المحال عليه المناقصة باي من الالتزامات، يحق للشركة الغاء الاحالة واللجوء الى طرف ثالث دون الحاجة لأي اخطار او اذار عادي او عدلي ودون الحاجة لمراجعة القضاء وتحميل المتعهد كافة التكاليف المترتبة على ذلك.
16. إذا عجز المورد المحال عليه المناقصة عن التوريد أو تأخر في تقديم كمية من أصل المناقصة أو عجز عن تقديم أية كمية في وقتها المحدد أو إذا ثبت أن أحد المناقصين قدم للشركة لوازماً أو قام بأداء خدمات بطرق الغش، لشركة مصفاة البترول الحق بما يلي:
 - مصادرة كفالة حسن التنفيذ المقدمة للمناقصة أو جزء منها، وقيد المبلغ المصادر إيراداً لحساب الشركة.
 - القيام بشراء اللوازم من الأسواق المحلية أو الأجنبية بالأسعار الرائجة والرجوع على المناقص بفرق السعر وخضم ذلك من الكفالة أو إحالة المناقصة او جزء منها على السعر الذي يليه مع تحميل المستنكف فرق السعر.
 - حرمان المناقص من الدخول في العطاءات/ المناقصات للمدة التي تراها الشركة مناسبة.
17. تعتبر هذه الشروط جزءاً لا يتجزأ من المناقصة وعلى المورد الالتزام بما جاء فيها.



شركة مصفاة البترول الاردنية المساهمة المحدودة

عمان - الأردن

18. اخر موعد لقبول واستلام العروض الرابعة عصرا من يوم الخميس 2026/09/10 وتسلم لدائرة المشتريات - الادارة العامة -

جبل عمان - الدوار الأول -الطابق الأول - مكتب 10

19. في حال وجود أي استفسار يتم إرساله بالبريد الإلكتروني على العنوان (Local.Purchasing@jopetrol.com.jo).

20. يجب ان تكون الفاتورة المقدمة من قبلكم في حال شراء السلع او تقديم خدمة وفقا" لنظام تنظيم شؤون الفوترة والرقابة عليها رقم (34) لسنة 2019 وسيتم رفض أي فاتورة لا تكون وفقا" للنظام أعلاه.

كما يشترط تقديم البيانات التالية على الفواتير الصادرة من قبلكم: -

الاسم الكامل للشخص أو الشركة أو المفوض بالتوقيع وختم الشركة الرسمي او المفوض بالتوقيع وتوقيعه.

الرقم الوطني الكامل للشخص أو الشركة أو المفوض بالتوقيع.

العنوان الكامل بالإضافة إلى رقم الهاتف والصندوق البريدي والرمز البريدي.

الرقم الضريبي للشخص أو الشركة إن وجد.

Jordan Petroleum Refinery Company
Quote OrderDate 13/08/2026
Page - 1

Order Number 26010280 OQ 00001

Delivery Instructions

Branch/Plant 2002
Order Date 13/08/2026
Request Date 01/02/2027
Freight Handling

General Description 1 161090 LED LIGHTING FIXTURES SUITABLE FOR LED TUBE LAMP
200-240VAC, 50HZ
METAL BODY, WHITE COLOR
COMPLETE WITH T8 LED LAMP(S). COLOR TEMPERATURE 6500K
LAMP SHALL BE GLASS.
PHASE SHALL BE FROM ONE SIDE AND NUTRAL FROM OTHER SIDE
(PHASE AND NAUTRAL ON THE SAME SIDE IS NOT ACCEPTABLE)
CONNECTED AND READY TO USE.
WARRANTY : 2 YEARS.

General Description 2

Line No.	VOCAB Number	Description	Part Number	Drawing Number	Ordered Quantity	Supplier Offer Unit Price	Supplier Offer Currency Code	Original Order No	Orig Type	LineNo
1	1603605063	Led lighting fixture, 2X20 Wat			100.000 EA			26010514 OR		1
2	1603605064	Led lighting fixture, 1X20 Wat			50.000 EA			26010514 OR		2

General Description 1 161091 T8 led tube lamp glass
200-240VAC, 50HZ
cool white color 6000K, lifespan: 25000 hours
The lamps shall be compatible to be installed on old fluorescent
lighting fixtures without removing the ballasts (plug and play mode)
Cap-base : G13 [medium Bi-Pin to replace fluorescent lamps]
Lamps shall be operated without starters
phase from one side and nutral from other side
TUV, CE marking, ROHS compliance
Warranty : 3 years.

General Description 2

3 1603605068 GLASS LED TUBE LAMP, 120 CM, 1850 LM

500.000 EA 26010514 OR 3

Jordan Petroleum Refinery Company
Quote Order

Date 13/08/2026
Page - 2

Order Number 26010280 OQ 00001

Line No.	VOCAB Number	Description	Part Number	Drawing Number	Ordered Quantity	Unit	Supplier Offer Unit Price	Supplier Offer Currency Code	Original Order No	Orig Type	LineNo
General Description 1											
161139		LED light bulbs: - base type: E27, power supply: 230V, 50 Hz - led efficiency : 80 lm/W (min.) - life span :15000hr (min.) - Samples shall be provided - Warranty: one year.									
General Description 2											
4	1603605082	LED Lamp, green, 9W			100.000	EA			26010514	OR	4
General Description 1											
161037		PENDANT TYPE EXPLOSION PROOF HEAVY DUTY LED LUMINAIRE FIXTURE. EX DESIGNATION: ExdembIIC T5 GB,IP66,I12GD,AND /OR CLASS I, DIVISION 1, GROUPS C, D OPERATING VOLTAGE: 100-277V AC 50Hz. POWER CONSUMPTION : 36W. POWER FACTOR : 0.98 TEMPERATURE RATING: -10°C +50°C. LUMENS OUTPUT : 3500 AT LEAST COOL WHITE LIGHT. FIXTURE MATERIAL : METALLIC ANTI CORROSIVE. CABLE ENTRY: FROM BOTH SIDES, THREAD SIZE:3/4" IT SHALL BE PROVIDED COMPLETE WITH FIXING ACCESSORIES AND ANY STARTING ELECTRONICS. LENS: HIGH IMPACT RESISTANT CLEAR GLASS. IT SHALL BE SUPPLIED WITH FIXING ADJUSTABLE BRACKET. IT SHALL BE SUPPLIED WITH A COPY OF EXPLOSION PROOF EU-TYPE EXAMINATION CERTIFICATE ISSUED FROM A NOTIFIED BODY AND LIGHTING FACTORY TEST REPORTS. LOCATION : TO BE USED FOR HAZARDOUS AREA LIGHTING INSIDE UNITS, LIGHTING INSIDE CLASSIFIED HAZARDOUS AREA GENERALLY.									
General Description 2											
5	1603605060	EXPLOSION PROOF LED LIGHTING			10.000	EA			26010514	OR	5

Jordan Petroleum Refinery Company
Quote Order

Order Number 26010280 OQ 00001

Line No.	VOCAB Number	Description	Part Number	Drawing Number	Ordered Quantity	Unit	Supplier Offer Unit Price	Supplier Offer Currency Code	Original Order No	Orig Type	LineNo
----------	--------------	-------------	-------------	----------------	------------------	------	---------------------------	------------------------------	-------------------	-----------	--------

General Description 1 161069 LED Explosion proof lighting fixtures
Power: 45 W,
Voltage range: 90-264VAC,
Rated frequency: 50Hz Max.
Minimum Marking: Ex II2GD Ex d IIC T4 Gb Ex tb IIIC T135 °C Db
Cable entries: 3/4-inch NPT threaded, Ingress protection: IP66
Operating temperature: -40 to +55 °C Service life: >50000 hour.
Color temperature: COOL white 6500K, Luminous efficiency: >130 Lm/W.
Power factor: >0.95 Luminous flux>5500 Lm. THD: <15%.
Beam angle: 140 Degree.
Standards: IEC 60079-0, IEC 60079-1, IEC 60079-31.
Each fixture shall be provided complete with driver, explosion proof Three entry connection box, a secure carrying string, and explosion proof male-female nipple for ceiling type installation.
Sample Shall Be Provided for Test.
The warranty period for the fixtures shall be not less than five years.
Manufacturer shall provide the following documents with his offer:
1. Tests reports explain the lux reading for 3m and 4m height.
2. Technical data sheet including dimensions
3. Installation and maintenance instructions.
4. EU-Type examination certificate for the fixture, connection box and nipple.
5. EU-Certificate of conformity with applicable standards
6. Manufacturer quality control plan

General Description 2

6	1604019050	Explosion proof led lighting,	Exd IIC T6	250.000 EA	26010514 OR	6
---	------------	-------------------------------	------------	------------	-------------	---

Purchasing Manager :

Remarks of Purchasing Department :

Order No: OR-26010514

No.	Vocab Number	Description	UOM	Quantity	Conformity	Deviations
1	1603605063	Led lighting fixture, 2X20 Wat	EA	100.000		
2	1603605064	Led lighting fixture, 1X20 Wat	EA	50.000		
3	1603605068	GLASS LED TUBE LAMP,	EA	500.000		
4	1603605082	LED Lamp, green, 9W	EA	100.000		
5	1603605060	EXPLOSION PROOF LED LIGHTING	EA	10.000		
6	1604019050	Explosion proof led lighting,	EA	250.000		

Order No. (26010514)

(Each point must be confirmed/ commented upon and must be submitted along with the offer)

SN	Requirement	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
1	Manufacturer name	
2	Full address	
3	Supplier name	
4	Full address	
5	Offer no.	
6	Offer validity (at least 90 days from closing date)	
7	Indicate the quoted currency.	
8	Indicate Country of Origin of goods offered	
9	Accordance to Jordan prevailing law, you should pay 6 per thousand of the total order to cover the REVENUE STAMPS	
10	Promised delivery date shall be provided.	
11	Price Inclusive/Exclusive Sales Tax	
12	Local supplier registration in the National E-Invoicing System	

OR NO. (26010514), OQ NO. () (Each point must be confirmed/commented upon and must be submitted with the offer)	
TECHNICAL REQUIREMENTS	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
LED LIGHTING FIXTURES SUITABLE FOR LED TUBE LAMP	
200-240VAC, 50HZ	
METAL BODY, WHITE COLOR	
COMPLETE WITH T8 LED LAMP(S), COLOR TEMPERATURE 6500K	
LAMP SHALL BE GLASS.	
PHASE SHALL BE FROM ONE SIDE AND NUTERAL FROM OTHER SIDE (PHASE AND NAUTERAL ON THE SAME SIDE IS NOT ACCEPTABLE)	
CONNECTED AND READY TO USE.	
WARRANTY : 2 YEARS.	
Item (1) Led lighting fixture, 2X20 Wat , 120 CM Quantity (100) EA	
Item (2) Led lighting fixture, 1X20 Wat , 120 CM Quantity (50) EA	

OR NO. (26010514), OQ NO. () (Each point must be confirmed/commented upon and must be submitted with the offer)	
TECHNICAL REQUIREMENTS	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
T8 led tube lamp glass	
200-240VAC, 50HZ	
cool white color 6000K, lifespan: 25000 hours	
The lamps shall be compatible to be installed on old fluorescent lighting fixtures without removing the ballasts (plug and play mode)	
Cap-base : G13 [medium Bi-Pin to replace fluorescent lamps]	
Lamps shall be operated without starters	
phase from one side and nuteral from other side	
TUV, CE marking, ROHS compliance	
Warranty : 3 years.	
Item (3) GLASS LED TUBE LAMP, 120 CM, 1850 LM Quantity (500) EA	

OR NO. (26010514), OQ NO. () (Each point must be confirmed/commented upon and must be submitted with the offer)	
TECHNICAL REQUIREMENTS	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
LED light bulbs:	
- base type: E27, power supply: 230V, 50 Hz	
- led efficiency : 80 lm/W (min.)	
- life span :15000hr (min.)	
- Samples shall be provided	
- Warranty: one year.	
Item (4) LED Lamp, green, 9W Quantity (100) EA	

OR NO. (26010514), OQ NO. () (Each point must be confirmed/commented upon and must be submitted with the offer)	
TECHNICAL REQUIREMENTS	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
PENDANT TYPE EXPLOSION PROOF HEAVY DUTY LED LUMINAIRE FIXTURE.	
EX DESIGNATION: ExdembIIIC T5 GB,IP66,II2GD.AND /OR CLASS I, DIVISION 1,GROUPS C,D	
OPERATING VOLTAGE: 100-277V AC 50Hz.	
POWER CONSUMPTION : 36W.	
POWER FACTOR : 0.98	
TEMPERATURE RATING: -10°C +50°C.	
LUMENS OUTPUT : 3500 AT LEAST COOL WHITE LIGHT.	
FIXTURE MATERIAL : METALLIC ANTI CORROSIVE.	
CABLE ENTRY: FROM BOTH SIDES,THREAD SIZE:3/4"	
IT SHALL BE PROVIDED COMPLETE WITH FIXING	
ACCESSORIES AND ANY STARTING ELECTRONICS.	
LENS: HIGH IMPACT RESISTANT CLEAR GLASS.	
IT SHALL BE SUPPLIED WITH FIXING ADJUSTABLE BRACKET.	
IT SHALL BE SUPPLIED WITH A COPY OF EXPLOSION PROOF EU-TYPE	
EXAMINATION CERTIFICATE ISSUED FROM A NOTIFIED BODY AND LIGHTING	
FACTORY TEST REPORTS.	
LOCATION : TO BE USED FOR HAZARDOUS AREA LIGHTING INSIDE UNITS,	
LIGHTING INSIDE CLASSIFIED HAZARDOUS AREA GENERALLY.	
Item (5) EXPLOSION PROOF LED LIGHTING FIXTURE230V,50HZ,36W,3500LUMEN Quantity (10) EA	

OR NO. (26010514), OQ NO. () (Each point must be confirmed/commented upon and must be submitted with the offer)	
TECHNICAL REQUIREMENTS	Vendor's confirmation/ acceptance/ comments to be mentioned for each item
LED Explosion proof lighting fixtures	
Power: 45 W,	
Voltage range: 90-264VAC,	
Rated frequency: 50Hz Max.	
Minimum Marking: Ex II2GD Ex d IIC T4 Gb Ex tb IIIC T135 °C Db	
Cable entries: 3/4-inch NPT threaded, Ingress protection: IP66	
Operating temperature: -40 to +55 °C Service life: >50000 hour.	
Color temperature: COOL white 6500K, Luminous efficiency: >130 Lm/W.	
Power factor: >0.95 Luminous flux>5500 Lm. THD: <15%.	
Beam angle: 140 Degree.	
Standards: IEC 60079-0, IEC 60079-1, IEC 60079-31.	
Each fixture shall be provided complete with driver, explosion proof Three entry connection box, a secure carrying string, and explosion proof male-female nipple for ceiling type installation.	
Sample Shall Be Provided for Test.	
The warranty period for the fixtures shall be not less than five years.	
Manufacturer shall provide the following documents with his offer:	
1 . Tests reports explain the lux reading for 3m and 4m height.	
2.Technical data sheet including dimensions	
3.Installation and maintenance instructions.	
4.EU-Type examination certificate for the fixture, connection box and nipple.	
5.EU-Certificate of conformity with applicable standards	
6.Manufacturer quality control plan	
Item (6) Explosion proof led lighting, Exd IIC T6 Quantity (250) EA	